
Alumagic 510







Specifications

Specifications

Length Width Dry weight Board height on the midship Keel angle on the transom Hull draft Transom height Maximum engine power Hull material Thickness (bottom/side) Number of passengers Boat weight in the state of maximum load Fuel tank Aerator box (I)


Value

- 5.1 m
- 1.96 m
- 595 kg
- 0.84 m
- 14
- 0.35 m
- 506 1111
- 100 hp
- AlMg 4,5 Mn (5083)

Livewell - 100 L

- 3 / 4 mn
- 4
- 1440 kg
- 90 |
- 100 l

Варіанти комплектації



Alumagic 510 fish platform



Basic Configuration

- all-welded hull with two consoles made of marine grade aluminum AlMg4.5Mn (5083) 3-4 mm thick

 outer sides and wind protection are painted in one color with Akzo Nobel special paint (color to choose from the proposed palette)

- protective wear-resistant coating LINE-X® on the panels / or corrugated aluminum flooring

- aluminum wind protection with gate and tempered glass

- inner sides in the cockpit and under the console space are covered with marine-grade carpet

- fuel system with an aluminum tank with a volume of 90 liters

- glove compartment in the passenger console with lighting and locking with a key

lockers with preparation for communications:
starting battery (1 pc.) + service battery (1 pc.) + traction
batteries (2 pcs.) for winch / electric anchor

- a 100-liter aerator box with connected communications

- 2 Premium High Back seats on a swivel base with back and forth adjustment mounted on lockers

- 2 Premium High Back seats on racks / or Fish Platform (depending on the configuration)

- stainless steel ladder in the stern

- USB sockets on the captain's and passenger's console

